

Horizontal Sliding Window **Series 2009-HS**

Window tested to design pressures of +110 psf and -150 psf with 7/16" glass and +/- 80 psf with 5/16" glass according to Miami-Dade County protocols TAS 201, 202 and 203. NOA 11-0513.01. Water tested to 16.5 psf.

Maximum window size is 96 x 74 in either XO or OX configurations and 142 x 74 in XOX configurations using 7/16" glass

Maximum window size is 74 x 64 in either XO or OX configurations and 111 x 74 in XOX configurations using 5/16" glass

Unique glass barrier insert panel is available to permit sill to set on the finished floor when using 7/16" glass type window

- Aluminum is extruded 6063-T6 alloy
- Popular glass tints available in 7/16" laminated glass
- Frame and sash are interlocked
- Stainless steel assembly screws
- Frame member depth is 2 3/4"
- Windows provided with a 1/2" flange
- Sash member depth is 1"
- Glazing is exterior
- Standard, modular and custom sizes are available
- Standard finish is E.S.P. painted white or bronze. Custom painted colors available
- Windows are double weather-stripped
- Sweep locks are standard for non-egress windows
- Side mounted snap lift latches are provided for egress windows
- Stainless Steel tandem rollers are standard
- Baffled weep slots for water evacuation are standard to reduce air movement and insect access
- Non-corrosive and finished materials are used throughout the window
- Applied single or double muntins available
- Windows are fitted with snap-out screens to ensure complete package

Florida Coastal Protective Manufacturing reserves the right to change materials, design and/or construction without notice or liability